

MATERIAL SAFETY DATA SHEET

CHEMCO INDUSTRIES, INC.
5731 Manchester Ave., St. Louis, MO 63110



DATE OF ISSUE: January, 05, 2006

GENERAL INFORMATION # : 314-647-1888
EMERGENCY TELEPHONE # : (800) 854-4236

I-PRODUCT IDENTIFICATION

COIL-X (AEROSOL)

PRODUCT CODE: #060N

CHEMICAL FORMULATION: COIL CLEANER

NFPA HAZARD IDENTIFICATION SYSTEM:

HEALTH: 2

FLAMMABILITY: 1

REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - HAZARDOUS INGREDIENTS

Hazardous Components (Specific Chemical Identity; Common Name (s))	CAS #	OSHA PEL	ACGIH TLV	Other Limits	
				Recommended	% optional
DIETHYLENE GLYCOL MONOETHYL ETHER*	111-90-0	N/E	N/E		1-3%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	50ppm	25ppm		1-3%
PROPANE	74-98-6	1000ppm	1000ppm		
ISOBUTANE	75-28-5	N/E	800ppm		

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling Level STEL: Short Term Exposure Limit

N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No

302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III/ List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).

372: SARA TITLE III/ List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - PHYSICAL DATA

BOILING POINT (C/F): N/A	MELTING POINT: N/A
VAPOR PRESSURE (psig @ 25 C) 50	SPECIFIC GRAVITY (WATER = 1): 1.02
CORROSION RATE: N/A	FREEZING POINT: N/A
VAPOR DENSITY (AIR = 1): >1	VOC CONTENT (% by weight): N/A
SOLUBILITY IN WATER: SOLUBLE	EVAPORATION RATE (Butyl Acetate = 1): <1
	pH (@ 25 C): 11.8
APPEARANCE AND ODOR: WHITE FOAM-SWEET ODOR	

IV - FIRE AND EXPLOSION HAZARD

FLASH POINT (F/C): NONE

(TEST METHOD):

FLAMMABLE LIMITS: N/E

UPPER: N/A

LOWER: N/A

EXTINGUISHING MEDIA: CO₂ STANDARD FOAM, DRY CHEMICAL, HALON.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARD: EXPOSURE TO TEMPERATURES OVER 120°F MAY CAUSE BURSTING OR VENTING. HEAT OR FIRE MAY CAUSE HAZARDOUS FUMES. CARBON MONOXIDE.

V - REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY: OXIDIZING MATERIALS

CONDITIONS TO AVOID: SOURCES OF HEAT

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: OPEN FLAMES MAY PRODUCE CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: N/A

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: COIL-X (AEROSOL)

PRODUCT CODE: #60A

VI - HEALTH AND HAZARD DATA

ROUTES OF ENTRY: INHALATION? SKIN? INGESTION?

HEALTH HAZARDS (ACUTE & CHRONIC):

CARCINOGENICITY: NTP?N/A IARC MONOGRAPHS?N/A OSHA REGULATED? N/A

EFFECTS OF OVEREXPOSURE

IF IN EYES: MAY CAUSE IRRITATION, REDNESS, OR WATERING

IF ON SKIN: MAY CAUSE ITCHING, DRYNESS, REDNESS, OR IRRITATION

IF SWALLOWED: NAUSEA, HEADACHE, VOMITING

IF INHALED: LARGE AMOUNTS OF VAPORS MAY CAUSE NAUSEA, OR DIZZINESS

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION

IF ON SKIN: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION

IF SWALLOWED: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

IF INHALED: REMOVE TO FRESH AIR

VII - SPILL AND LEAK PROTECTION

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. DIKE AREA IF POSSIBLE FOR MATERIAL RECOVERY. SMALL QUANTITIES MAY BE ABSORBED WITH ABSORBENT MATERIALS.

WASTE DISPOSAL METHOD: DISPOSE OF IN A MANNER APPROVED BY LOCAL, STATE AND FEDERAL REGULATIONS AS WELL AS EPA STANDARDS

VIII - SPECIAL PROTECTION INFORMATION

VENTILATION: GENERAL VENTILATION RECOMMENDED TO MAINTAIN THE LEVEL OF THE HAZARDOUS INGREDIENTS TO LESS THAN HALF OF THE TLV.

RESPIRATORY PROTECTION: NOT REQUIRED

PROTECTIVE GLOVES: RUBBER GLOVES

EYE PROTECTION: SAFETY GOGGLES. FOR SHORT USAGE NONE REQUIRED.

OTHER PROTECTIVE EQUIPMENT: NONE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: DO NOT STORE WHERE TEMPERATURES EXCEED 120°F.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

WORK/HYGIENIC PRACTICES :

REVISION DATE: January 05, 2005

Prepared By:

DATE OF ISSUE: January 05, 2005

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Chemco Industries assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.